



АВАРИЙНЫЙ ДУШ С БАКОМ ОБЪЕМОМ 1500L

МОДЕЛЬ: TS1500

ANSI Z358.1-2014 EN15154-1, 18.5-8&A

6&, 1&&

The unit is completely corrosion resistant and suitable for hazardous or non-hazardous environments. Comes with water level indicator and testing lever as standard.

KEY FEATURES

- Over 15 minutes tepid water
- Manufactured in house, in the UK
- Photoluminous pictorial signs
- One-piece insulated GRP header tank



MADE IN BRITAIN

Показано с опциональным фонтаном для промывки глаз, панелями и ножной платформой

OPERATING CONDITIONS

WATER SUPPLY PRESSURE 0.5 - 6 bar

TEMPERATURE -25°C to +55°C (water chiller recommended for temperatures above 35°C)

TECHNICAL DETAILS

INLET CONNECTION 1" BSPM (flanged options available)

SHOWER DRAIN OUTLET CONNECTION - if fitted 2" BSPF

SCREENED OVERFLOW 40mm PVC-U

SHOWER FLOW RATE 76lpm

EYEBATH FLOW RATE Min 1.5lpm

BALL FLOAT VALVES for quick refill 2 x 3/4" brass valves with 6" plastic floats

SHOWER OPERATION Panic bar (GRP foot platform as option)

EYEBATH OPERATION Lift lid (stainless foot operation as option)

SIGNAGE Self-adhesive photoluminous pictorial sign

MATERIAL DETAILS

HEADER TANK 1500L green insulated GRP (other colours available)

HEADER TANK LID White insulated GRP

SHOWER FRAME 304 stainless steel as standard (316 as option)

OPERATING VALVES Stainless steel

SHOWER ROSE Yellow - ABS (stainless as options)

PANIC BAR/TESTING LEVER Stainless steel (powder coated red for high visibility)

PANELLING - if fitted Side & rear - green GRP

SHOWER PLATFORM - if fitted Yellow non-slip GRP

OVERHEAD SUN CANOPY - if fitted White insulated GRP

EYEBATH - if fitted Yellow GRP + 2 low pressure nozzles




EYEBATH FOOT TREADLE - if fitted Stainless steel (powder coated red for high visibility)

TEMPERATURE GAUGE - if fitted Stainless steel - 150mm diameter

WATER HEATER - if fitted 2.4Kw (Non-hazardous)



OPTIONAL EXTRAS



TECHNICAL DRAWINGS

